

DANTHERMGROUP



DH 792

Condensation dehumidifiers

Sturdy and cost-effective, the DH 792 are robust portable dehumidifiers which come with the option of connecting a water pump and draining the condensate via a hose and have a built-in hour meter as well as hygostat. Ideally suited for projects in the construction industry, restoration jobs, water damage control and rental jobs.



Master DH 792



Master dehumidifiers applications video

Key features

- ✓ Automatic fast defrosting using hot gases
- ✓ High efficiency
- ✓ Durable casing
- ✓ Simple operation
- ✓ Built-in hygostat
- ✓ Continuous operation possible (24 h/day)

- ✓ Water tank with automatic shut-off when full
- ✓ Possibility to connect a hose to remove condensed water
- ✓ Hour counter
- ✓ Air filter

Product specifications

Specifications	Units	DH 792
Capacity (30°C/80% RH)	l/24h	100
Capacity (20°C/60% RH)	l/24h	44.6
For rooms of approx.	m ³	1,500
For restoration after flood	m ³	600
Refrigerant	-	R454C
Air flow	m ³ /h	1,000
Operating temperature range	°C	5-35
Operating humidity range	%	35-90
Power consumption	W	1,840
Power supply	V/Hz	220-240/1ph/50
Sound level	dB(A)	69
Compressor		Rotary
Tank capacity	l	15
Product size (l x w x h)	mm	620 x 540 x 1095
Box size (l x w x h)	mm	730 x 526 x 1150
Net/gross weight	kg	64/70
Pallet	pcs	2

