

Electric fan air heaters

B 18-30, RS 40

MASTER
CLIMATE SOLUTIONS

B 18
B 30



PATENT

RS 40



- Possible connection to a flexible tube
- Lifting eyelets for easy transport (B 30)
- Manual reset
- Built-in room thermostat (RS 40)
- No oxygen consumption
- No fumes, no odours, no humidity
- Summer/Winter switch for ventilation only
- Motor with thermal protection
- Overheat thermostat
- Adjustable heat

Optional accessories



**Analogue thermostat
TH5 with cable**
3m - **4150.109**
10m - **4150.112**



Extension cord
B 18 - 32A, 5m - **4515.333**
B 18 - 32A, 10m - **4515.334**
B 30, RS 40 - 63A, 5m - **4515.335**
B 30, RS 40 - 63A, 10m - **4515.336**



PVC flex tubes 1-way outlet
B 18 - Ø305mm - 7.6m - **4515.553**
B 18 - Ø305mm - 3m - **4515.572**
B 30 - Ø407mm - 3m - **4515.571**
B 30 - Ø407mm - 7.6m - **4031.401**
RS 40 - Ø508mm - 7.6m - **4515.552**

PVC flex tubes 2-way outlet
B 18 - 2 x Ø230mm - **4515.557**
B 30 - 2 x Ø305mm - **4515.553**



2-way outlet
B 18 - Ø230mm -
4511.808
B 30 - Ø300mm -
4511.807



Adaptor ring kit
RS 40 - **4210.180**



NYLON flex tube with bag
B 18 - Ø305mm - 7.6m - **4515.360**
B 30 - Ø407mm - 7.6m - **4515.361**
RS 40 - Ø508mm - 7.6m - **4515.366**

Electric fan air heaters
B 18-30, RS 40



Specifications	Units	B 18	B 30	RS 40
Heating power	kW	9/18	15/30	13/26/40
	Btu/h	30,700-61,400	51,200-102,400	44,360-136,500
	kcal/h	7,740-15,480	12,900-25,800	11,200-34,400
Air flow	m ³ /h	1,700	3,500	3,100
Power supply	V/Hz	400/3ph/50-60	400/3ph/50	380-400/3ph/50
Plug (male) from heater side		32A/5P	63A/5P	63A/5P
Rated current	A	26.0	43.5	58.0
Switch pos. 1		Off	Off	Fan
Switch pos. 2		Fan	Fan	13 kW
Switch pos. 3/4	kW	9/18	15/30	26/40
Thermostat control		Optional TH5	Optional TH5	On board
Temperature range	°C	< 25	< 25	-30 - +35
Protection		IP24	IP24	IP20
Product size (l x w x h)	mm	700 x 490 x 530	1030 x 580 x 680	990 x 710 x 800
Box size (l x w x h)	mm	600 x 400 x 460	1050 x 600 x 820	870 x 630 x 770
Net/gross weight	kg	27/29.3	53/63	46/52
Pallet	pcs	16	1	6