


Professional blowers
BLM 4800-6800



BLM 4800



BLM 6800



- Robust and durable construction
- Metal casing
- Easy to use and transport
- High air flow
- Motor with thermal protection
- Possibility to connect flexible tubes on inlet and outlet side

Optional accessories



PVC flex tubes 7.6m
 BLM 4800 - Ø250mm - **4515.559**
 BLM 6800 - Ø340mm - **4515.560**



Dust bag - 3m length
 BLM 4800 - **4515.540**
 BLM 6800 - **4515.541**
 Dust bag filtration level - EPA 10

Specifications	Units	BLM 4800	BLM 6800
Air flow	m ³ /h	1,500	3,900
Max. air pressure	Pa	245	373
Fan	type	Axial	Axial
Fan speed		1	1
Power consumption	W	230	350
Power supply	V/Hz	220-240/1ph/50	220-240/1ph/50
Outlet diameter	Ømm	230	320
Inlet diameter	Ømm	250	340
Air current		Blow out/suction	Blow out/suction
Protection		IP44	IP44
Product size (l x w x h)	mm	250 x 305 x 230	343 x 383 x 317
Box size (l x w x h)	mm	265 x 335 x 350	365 x 405 x 340
Net/gross weight	kg	6.4/8	9.5/10.5
Pallet	pcs	40	24