EKO 3



EKO 3





- Compact and lightweight (19kg)
- EKO 3 delivers 800m³/h of hot air using only 2.8 kW at 240 V (single phase)
- Connection to the external digital remote thermostat THK, specific for this application, included in the box
- Overheat thermostat
- Motor with thermal protection and intervention
- The Master EKO is placed inside the room and recirculates the air, gradually increasing the temperature
- Recommended for: hotels, hostels, smaller rooms, vans, hospitals, restaurants, bakeries, commercial kitchens
- Fighting bugs using heat is safe for people and the environment
- EKO heaters are able to maintain the temperature above 45°C. This is required to carry out total pest eradication.
- The high air flow allows a fast increase and an even temperature distribution in the room

Included in the box



Remote thermostat THK with probe
4150.137

EKO works on the fact that bugs, larvae and eggs die of dehydration when kept at a temperature above 45°C degrees for a few hours.

EKO 3 is designed to be used in very small spaces or as a support to an EKO 9.

Specifications	Units	EKO 3
Heating power	kW	2.8
	Btu/h	11,260
	kcal/h	2,866
Air flow	m³/h	800
Power supply	V/Hz	230/1ph/50
Rated current	A	12.4
Remote thermostat		Digital
Product size (l x w x h)	mm	455 x 440 x 600
Box size (l x w x h)	mm	500 x 400 x 655
Net/gross weight	kg	19/24
Pallet	pcs	12