

INDUSTRIAL VACUUM CLEANERS

SKY 2000 - 2500 - Aspiratore per nebbie oleose - Potenza alta - OIL AND CHIPS



METALWORKING



OEM ORIGINAL EQUIPMENT MANUFACTURERS



- ✓ Compact, powerful and light.
- ✓ Reduced electrical consumption
- ✓ Easy and fast maintenance.
- ✓ Easy mount on the machine.
- ✓ Quick and easy filter replacement system.



SUCTION UNIT

Voltage	V - Hz	400 - 50
Power	kW	0,75 - 1,1
Electrical protection	IP	55
Max air flow	m ³ /h	2000 - 2500
Suction inlet	mm	200
Noise level (EN ISO 3744)	dB(A)	74 - 76



FILTER UNIT

Filter Type	Cartridge	
Surface - Diameter	cm ² -mm	100.000
Material - Efficiency	IEC 60335-2-69	M - PTFE
Cartridge number	1	



VOLUME

Dimensions	cm	56 x 50,8h
Weight	kg	41,5 - 43,0



SUCTION UNIT

The suction unit is a low power turbine with high air flow.



FILTER UNIT

Filtration versatility: multilayer filter (standard) or pleated high-surface filter cartridge with coalescent pre-filter



COLLECTION UNIT

The extracted and filtered oils and emulsions are thickened on the wall of the vacuum cleaner allowing recovery by drainage pipe.



OPTIONALS

- ✓ Installation kit with riser.
- ✓ Installation kit with adjustable riser.
- ✓ Wall mounting kit.
- ✓ Column stand adjustable from 1.5 to 2.5 meters for fixing to the floor.
- ✓ Kit Cyclon Pre-filter
- ✓ Kit Hepa H13 Final filter efficiency 99,95%