

INDUSTRIAL VACUUM CLEANERS

SKY 250 - 500 - Aspiratore per nebbie oleose - OIL AND CHIPS



METALWORKING



OEM ORIGINAL EQUIPMENT MANUFACTURERS



- ✓ Compact, powerful and light.
- ✓ Reduced electrical consumption
- ✓ Easy and fast maintenance.
- ✓ Easy mount on the machine.
- ✓ Quick and easy filter replacement system.



SUCTION UNIT

Voltage	V - Hz	400 - 50
Power	kW	0,12 - 0,18
Electrical protection	IP	55
Max air flow	m³/h	250 - 500
Suction inlet	mm	100
Noise level (EN ISO 3744)	dB(A)	58 - 62



FILTER UNIT

Filter Type	Cartridge	
Surface - Diameter	cm²-mm	20.000
Material - Efficiency	IEC 60335-2-69	M - PTFE
Cartridge number	1	



VOLUME

Dimensions	cm	36x38,5h
Weight	kg	20,5 - 21,0



SUCTION UNIT

The suction unit is a low power turbine with high air flow.



FILTER UNIT

Filtration versatility: multilayer filter (standard) or pleated high-surface filter cartridge with coalescent pre-filter



COLLECTION UNIT

The extracted and filtered oils and emulsions are thickened on the wall of the vacuum cleaner allowing recovery by drainage pipe.



OPTIONALS

- ✓ Painted metal kit for Air outlet fan
- ✓ Installation kit with riser.
- ✓ Installation kit with adjustable riser.
- ✓ Wall mounting kit.
- ✓ Column stand adjustable from 1.5 to 2.5 meters for fixing to the floor.
- ✓ Kit Cyclon Pre-filter