EXPLOSION PROOF BLOWERS

EFI 75XX & UB 20XX (POWERVENT)

new product



EFI 75XX

new product



UB 20XX



- ATEX explosion-proof ventilator
- For harsh working conditions
- PC/ABS antistatic casing, weatherproof, flameretardant and chemical resistant
- High air flow
- Easy transport with comfortable handle
- Possibility to connect a flex tube
- Effective protection against dust and water
- Safely blow or exhaust hazardous gases with minimal risk of the fan causing a spark
- Atex certification: II 2 G Ex db eb IIB T6 Gb, II 2 G Ex IIB T6 Gb, Zone 1+2

Optional accessories



Flex tube, antistatic,7.6m
EFi 75xx - Ø305mm **-**
1250066
UB 20xx - Ø230mm **-**
1250099



Power cable adaptor, 1.5m
EFi 75xx, UB 20xx -
1450290



Duct canister antistatic incl. duct
7.6 m, Ø205mm **-**
UB 20xx- 1250211

Specifications	Units	EFi 75xx	UB 20xx
Air flow	m^3/h	4,250	1,392
Max. air pressure	Pa	314	195
Fan type		1 x Axial	1 x Axial
Fan speed		1	1
Power consumption	W	560	250
Power supply	V/Hz	220-240/1ph/50-60	230/1ph/50
Sound level	dB(A)	89	74
Flex tube diameter	cm	30.5	20.5
Protection		IP55	IP55
Product size (l x w x h)	mm	406 x 381 x 406	330 x 305 x 355
Box size (l x w x h)	mm	450 x 500 x 520	450 x 400 x 530
Net/gross weight	kg	20	8.2 / 15
Pallet	pcs	6	8