

# DH 721-732



DH 732



DH 721

- Digital control
- High efficiency
- Durable casing
- Simple operation
- Built-in hygrostat
- Continuous operation possible (DH 721)
- Water tank with automatic shut-off when full
- Possibility to connect a hose to remove condensed water
- Air filter
- DH 732 are stackable
- For rooms of approx. 390m<sup>3</sup> (DH 721) - 450m<sup>3</sup> (DH 732)

Specifications	Units	DH 721	DH 732
Capacity (30°C/80% RH)	l/24h	20	29
Capacity (20°C/60% RH)	l/24h	7	13
Air flow	m <sup>3</sup> /h	200	200
Operating temperature range	°C	5-35	5-35
Operating humidity range	% RH	35-90	35-95
Power consumption	W	490	465/339
Refrigerant	type	R290	R290
Power supply	V/Hz	220-240/1ph/50	220-240/1ph/50
Sound level	dB(A)	42	42
Compressor	type	Piston	Rotary
Tank capacity	l	4.7	6.5
Product size (l x w x h)	mm	335 x 305 x 580	358 x 338 x 550
Box size (l x w x h)	mm	380 x 350 x 640	402 x 387 x 592
Net/gross weight	kg	19/21	19.5/21
Pallet	pcs	18	18