

DH 752-792



DH 752



DH 792



- Automatic fast defrosting using hot gases
- High efficiency
- Durable casing
- Simple operation
- Built-in hygrostat
- Continuous operation possible (24 h/day)
- Water tank with automatic shut-off when full
- Possibility to connect a hose to remove condensed water
- Hour counter
- Air filter
- Suitable for spaces of approx. 701m³ DH 752, 1,500m³ DH 792

Optional accessories



Water pump
Max. forcing height - 4m
4512.442

Specifications	Units	DH 752	DH 792
Capacity (30°C/80% RH)	l/24h	48	100
Capacity (20°C/60% RH)	l/24h	21	44.6
Refrigerant	type	R290	R454C
Air flow	m ³ /h	350	1,000
Operating temperature range	°C	5-35	5-32
Operating humidity range	% RH	20-90	35-90
Power consumption	W	700/485	1,840
Power supply	V/Hz	220-240/1ph/50	220-240/1ph/50
Sound level	dB(A)	52	69
Compressor	type	Rotary	Rotary
Tank capacity	l	5.7	15
Product size (l x w x h)	mm	580 x 422 x 820	620 x 540 x 1095
Box size (l x w x h)	mm	610 x 405 x 660	730 x 526 x 1150
Net/gross weight	kg	30/36	64/70
Pallet	pcs	12	2