

DIRECT GAS FIRED AIR HEATERS – MECHANIC

BLP 17M-BLP 33M-BLP 53M-BLP 73M



Ventilation of the room is necessary to prevent a deficiency of oxygen.



PATENT



BLP 17M
BLP 33M
BLP 53M
BLP 73M



- Manual ignition
- Electrovalve
- Safety gas valve with thermocouple
- Regulator includes safety valve which stops the gas flow in the case of cracks in the gas tube
- Regulator and gas hose included
- Motor with thermal protection
- Overheat thermostat
- Adjustable heat
- Easy maintenance

The BLP 17 is provided with a heat and consumption knob. For other models, adjustment is possible using the gas regulator.

Optional accessories



Multiple bottles coupling set
DE/AT/DK/NL/PL:

Gas hose - **4515.901**
Gas regulator - **4515.902**

ES/HR/SI/CZ/HU/FR/CH/BE/SK/YU/BA/RO/BG/LT/LV/EE/BA/RU:

Gas hose - **4515.914**
Gas regulator - **4515.912**



Orientable frame
for BLP 33M-53M-73M -
4103.150



Specifications	Units	BLP 17M	BLP 33M	BLP 53M	BLP 73M
Heating power	kW	10-16	18-33	36-53	49-73
	Btu/h	34,200-54,800	61,500-112,800	123,000-181,000	167,100-249,300
	kcal/h	8,600-13,800	15,500-28,400	31,000-45,600	42,100-62,800
Pressure	bar	0.7	0.75-1.5	0.75-1.5	0.75-1.5
Ignition		Manual	Manual	Manual	Manual
Thermostat control		No	No	No	No
Air flow	m ³ /h	300	1,000	1,450	2,300
Fuel consumption	kg/h	1.16	2.4	3.78	5.02
Power supply	V/Hz	220-240/1ph/50	220-240/1ph/50	220-240/1ph/50	220-240/1ph/50
Electric power	kW	0.053	0.06	0.11	0.218
Rated current	A	0.23	0.26	0.48	0.95
Product size (l x w x h)	mm	471 x 188 x 293	552 x 220 x 342	605 x 276 x 444	685 x 276 x 444
Box size (l x w x h)	mm	550 x 230 x 300	600 x 250 x 360	680 x 300 x 510	760 x 300 x 510
Net/gross weight	kg	4.5/5.5	7.5/9	13/15	15/17
Pallet	pcs	49	36	16	16
Dual voltage		No	Available	Available	Available