

TC 400 IF

INDUSTRIAL VACUUM CLEANER FOR EMPTYING TANKS AND RESERVOIRS



Filter category:

FEATURES

Separation and recovery of oil and chips for machine tool maintenance
Easy to transport

Complete painted steel construction

Superweb 3D Kit, sieve grid basket for chip separation and polypropylene filter for liquids

Reversible flow liquid drain or submersible pump (with continuous suction and discharge)

All data mentioned in this document may change without notice. All data contained in this document is subject to change without notice.

DELFIN
FOR A DUST-FREE WORLD
www.delfinvacuums.com
delfin@delfinvacuums.it

COPYRIGHT 2026 DELFIN S.R.L. ALL RIGHTS RESERVED
COPYRIGHT 2026 DELFIN S.R.L. ALL RIGHTS RESERVED

TECHNICAL DATA

		TC400IF-001
Voltage	V	400
Power	kW	4.6
Frequency	Hz	50
Current draw	A	9.00
Suction inlet diameter	mm	50
Noise level	dB(A)	76
Dimensions	cm	145x70x180h
Weight	kg	225
Electrical protection	IP	65
Liquids capacity	L.	400
Solids capacity	L	50
Discharge capacity		200
Maximum vacuum	mmH2O	3200
Continuous waterlift	mmH2O	2600
Maximum air flow	m³/h	420
Motor Type		Three-phase Turbine
Primary filter		3D Superweb
Primary filter diameter	mm	500
Filter class (IEC 60335-2-69) primary filter		Polypropylene
Filtration	µm	20
Discharge system		Flow reversal
Automatic motor shutdown control		Yes

OPTIONAL

Code	Description
PPL300	PPL oil filter kit up to 300 microns (in suction)
OWR	Oil & water repellent cartridge
PUMP	300 l/min discharge with electric sensor
AUT.PUMP	Automatic discharge when the container is full (pump discharge is required)



COPYRIGHT 2026 DELFIN S.R.L. ALL RIGHTS RESERVED
COPYRIGHT 2026 DELFIN S.R.L. ALL RIGHTS RESERVED

MACHINE CODE	DESCRIPTION
TC400IF-001	TC 400 IF

All data mentioned in this document may change without notice. All data contained in this document is subject to change without notice.

DELFIN
FOR A DUST-FREE WORLD

www.delfinvacuums.com
delfin@delfinvacuums.it