

VACUUM CLEANERS FOR DIRECT DUST SUCTION FROM PROCESS MACHINERY

DBF RANGE - DBFV


The fixed vacuum bases on the machine are the ideal solution for removing powder and small scraps directly at the source during production cycles. Compact and available in vertical or horizontal construction, they are easy to install and integrate into existing or highly automated production lines.

BENEFITS:

- Continuous suction in order to avoid machine downtime and to maintain high productivity standards
- No powder releasing into the working environment
- Ergonomic and easy to use for thorough cleaning of the working area
- Minimal space requirements, modular construction



OPTIONAL



TECHNICAL DATA	DBFV 05	DBFV 10	DBFV 20	DBFV 30
Voltage/Power	400V - 50Hz 3~/ 0,4 kW	400V - 50Hz 3~/ 0,85 kW	400V - 50Hz 3~/ 1,8 kW	400V - 50Hz 3~/ 2,2 kW
Continuous waterlift	1500 - 1200 mmH ₂ O	2000 - 1400 mmH ₂ O	3000 - 2200 mmH ₂ O	2600 - 1900 mmH ₂ O
Max air flow	100 m ³ /h	150 m ³ /h	270 m ³ /h	318 m ³ /h
Filter	Polyester bag - M PTFE	Polyester bag - M PTFE	Polyester star - ANT M	Polyester star - ANT M
Capacity	15 lt	15 lt	25 lt	25 lt
Dimensions/Weight	50x33x73h cm / 30kg	50x33x73h cm / 35kg	54x55x103h cm / 40kg	54x55x103h cm / 45kg