ZFR EV AP 560 PN 4Kw - INDUSTRIAL THREE PHASE

CHEMICAL-PHARMACEUTICAL

ELECTRONICS

WINE

- ✓ Integrated filter cleaning system
- ✓ Complete steel construction
- ✓ Extractable collection container with optional use of disposable bags
- ✓ High filtration efficiency
- ✓ High air flow value
- ✓ Possibility of integration on other vacuum cleaners
- ✓ Conceived for the suction of fine dusts suspended in the air
- ✓ Optional articulated arm to suction in a restricted area

SUCTION UNIT

Voltage	V - Hz	400 - 50
Power	kW	4
Electrical protection	IP	55
Max water lift	mmH□O	200 / 300 / 350
Max air flow	m³/h	2.700 / 1.800 / 1.100
Suction inlet	mm	200 / 150 / 120
Noise level (EN ISO 3744)	dB(A)	74

FILTER UNIT

Filter Type		Cartridge
Surface - Diameter	cm²-mm	106.000 - 560
Material - Efficiency	IEC 60335-2-69	Polyester - ANT M
Cleaning system		Automatic PN

COLLECTION UNIT

Discharge system		Roll-out container
Capacity	lt	100

VOLUME

Dimensions	cm	78x85x250h
Weight	kg	140

All data mentioned in this document may change without notice.
Tutti i dati riportati in questo documento potrebbero variare senza preavviso

www.delfinvacuums.com
delfin@delfinvacuums.it

SUCTION UNIT

The suction unit is made of an electric fan which guarantees elevated air flow.

FILTER UNIT

Cartridges are automatically cleaned by a pneumatic reverse pulse cleaning system.The system is automatic, timed and adjustable. A compressor can be installed (on demand) on the back frame to guarantee the required air supply.

COLLECTION UNIT

The vacuum is assembled onto a sturdy steel chassis, and provided with industrial quality wheels , that make it suitable for mobile service even when used on rough surfaces.

OPTIONALS

- ✓ STAINLESS STEEL COLLECTION TANK
- ✓ EARTH GROUNDING
- ✓ OTHER VOLTAGES AND FREQUENCIES AVAILABLE UPON REQUEST
- ✓ ATEX CERTIFICATION
- ✓ EXTRACTION ARM
- ✓ DOUBLE EXTRACTION ARM

All data mentioned in this document may change without notice.
Tutti i dati riportati in questo documento potrebbero variare senza preavviso

www.delfinvacuums.com
delfin@delfinvacuums.it