




AB 200

The AB 200 is a ready to use side-channel blower with integrated vibration suppression and sound insulation, ideally suited for water damage restoration.

Control/operation

- On/Off-switch
- Amperemeter to show the counter pressure
- Device socket, fused 8A
- MID compliant energy metre



- Case made of stainless steel
- Easy to service and maintain
- Rubber feet for installation on the floor or other flat surfaces
- Lightweight and easy to carry
- The system is designed to deliver optimum performance using 50mm hoses with alternative 38mm hose fittings optional
- Coarse filter at suction side
- Very quiet due to highly efficient sound reduction system
- Integrated cable retention
- Can be used for suction or positive pressure drying of insulated constructions
- Cavity drying up to 10-15m²

Optional accessories



Superflextract hose
 50m - 2002247

Specifications	Units	AB 200
Air flow	m ³ /h	80
Max. operating temperature range	°C	0-38
Max. pressure differential		
Vacuum	mbar	110
Pressure	mbar	130
Noise level	dB(A)	<46
Total power consumption	W	400
Power supply	V/Hz	230/1ph/50
Power cord	m	4.5 with plug
Protection class		IP23
Pressure	mbar	110/130
Product size (h x d x w)	mm	330 x 310 x 365
Weight	kg	19