



TEH 200
TEH 300
TEH 400



- Extremely robust – top-quality product "made in Germany"
- Stackable
- Suitable for air transport hoses up to 100 metres
- Electronically-controlled multi-stage switch for air flow and air temperature
- Comes standard-equipped with protective frame, crane eyes, fork lift slits, transport wheels and parking brake
- Integrated thermostat control optional
- Overheating protection

Optional accessories



SP-T flex tube
457mm, 7.6m
6.100.001.214
600mm, 7.6m
6.100.001.218



SP connector nozzles
457mm
6.100.001.930
600mm
6.100.001.945



Tension strap
universal for SP series
2.5m - **6.100.001.995**



Air filter
TEH 200/TEH 300
7.710.001.2018
TEH 400
7.710.001.219



SP-C flex tube
600mm, 7.6m
6.100.001.273

Specifications	Unit	TEH 200	TEH 300	TEH 400
Heating capacity	kW	40	80	120
	kcal/h	34,394	68,788	103,181
Speed	kW	1,7	3	5,4
Air flow	m ³ /h	2,000	6,000	9,000
Air pressure	Pa	600	600	600
Power supply	V/Hz	400/50-60	400/50-60	400/50-60
Connection socket		CEE 63 A, 5-pole	125/CEE 125 A, 5-pole	200/direct connection
Air flow and temperature increase stages		8	8	8
Hose connector	Ømm	450	450	600
Thermostat control		Digital	Digital	Digital
Temperature range	°C	-20 to +40	-20 to +40	-20 to +40
Product size (l x w x h)	mm	1,625 x 800 x 1,270	1,625 x 800 x 1,270	2,000 x 1,300 x 1,450
Weight	kg	280	310	460